PROSUPPORT TUBE SLIMis a modular system to make outdoor floating floors from 10 to 40 mm height, it is composed of two bases of 10 mm height, levellers of 10 mm thickness and anti-noise and anti-slip disks. Thanks its modularity the system allows to make, from a height of 10 mm, all heights with 2 mm interval using the levellers.

PROSUPPORT SLIM SYSTEM





BASE WITH FLAPS PSTSB 04 - 4 mm

BASE WITH FLAPS PSTSB 02 - 2 mm

BASE with flaps 2/4 mm polypropylene - Pack 120 Pc

	Article	Thickness (mm)	Pcs/pack	
③	PSTSB 02	2	120	
③	PSTSB 04	4	120	



ANTI-NOISE AND ANTI-SLIP DISK

ANTI-NOISE AND ANTI-SLIP DISK rubber - pack. 120 pcs

Article	H/Ø mm	Pcs/pack	
PSTSG	H 1,5 - Ø 150	120	



LEVELLER PSTSL 02 - 2 mm

LEVELLER Polystyrone - Pack 120 Pc

	. orgacy, circ	1 dek 120 i d				
	Article	Thickness (mm)	Pcs/pack			
OPSTSL 02		2	120			


LAYING EXAMPLE

Example 1: final height 12 mm PSTB 04 + PSTSPL 02



Example 2: final height 24 mm 2 x PSTB 04 + 3 x PSTSPL 02







TECHINCAL LAYING INSTRUCTIONS

- 1. Place the bases with the flaps (max 4 pcs) PROSUPPORT
- 2. If necessary put on the bases the levellers to have the required height (max 4 pcs)
 3. Put on the support the anti-noise and anti-slip rubber disk

Example 3: final height 30 mm 3 x PSTB 04



