



KERAMAX

PORTABLE TILE CUTTING SAW FOR LARGE SIZED SLABS



PRODUCT DESCRIPTION

- 1500 W motor.
- 1300 mm cutting length
- Operates with Ø 250 mm blades for a precise cut.
- New cooling system, with adjustable nozzles.
- Anchoring system to immobilize slab while cutting.
- Easy bench removal (no tools needed).
- Foldable legs with leveling system.
- Front and rear handles.
- Rear wheels.

KERAMAX

Model	Blade bore (mm / Inch)	Max blade Ø (mm / Inch)	Blade included
Keramax 130	25,4 mm 1"	250 10"	Yes, 250 mm 10"
Keramax 160	25,4 mm 1"	250 10"	Yes, 250 mm 10"

RECOMMENDED BLADES



Keramax
Ø 250 mm
page 93



Gres continuous rim
Ø 250 mm
page 93



Bevel cut
Ø 250 mm
page 94



Cutting length 1300 and 1600 mm



Foldable support arms



Ø 250 mm blade (included)



Adaptable nozzles



Set of 2 adjustable clamps



Wheels and handles



4 clamps set



Foldaway adjustable legs



KERAMAX 130

Phase	Frequency Hz (plug pins)	Code	Motor voltage (V)	KW (HP)	Max. cutting length	Water tub capacity (L/Gal.)	Net weight Kg (Lbs)	Packaging dimensions LxWxH / mm (Inch)	Folding legs
1-PHASE	50 (2P)	0102003000	230						
1-PHASE	50 (3P)	0102003003	110	1,5 (2)	1300 mm (51")	49 / 13	90 (148,4)	1990 x 612 x 1300 (74,8" x 24" x 51")	Yes
1-PHASE U.S.A.	60 (3P)	0102003002	110						

KERAMAX 160

Phase	Frequency Hz (plug pins)	Code	Motor voltage (V)	KW (HP)	Max. cutting length	Water tub capacity (L/Gal.)	Net weight Kg (Lbs)	Packaging dimensions LxWxH / mm (Inch)	Folding legs
1-PHASE	50 (2P)	0102004000	230						
1-PHASE	50 (3P)	0102004003	110	1,5 (2)	1600 mm (63")	49 / 13	90 (148,4)	1990 x 612 x 1300 (74,8" x 24" x 51")	Yes
1-PHASE U.S.A.	60 (3P)	0102004002	120						

CUTTING CAPACITY KERAMAX

Model	Max. cutting depth	cutting depth to 90°	cutting depth to 45°
Keramax 130	53-63 mm (2"-2,4")	50 mm / 2"	40 mm (1,57")
Keramax 160	53-63 mm (2"-2,4")	50 mm / 2"	40 mm (1,57")