

**PROEND GRIP** is a non-slip step nosing profile in anodised aluminium with adhesive non-slip 20mm thick insert in black carborundum to be fitted in the relative groove in the top of the profile upon completion of laying. The profile may be laid with fixing screws hidden afterwards by the adhesive carborundum, or with silicone and/or adhesive to be applied on the bottom of the profile, which is designed to ensure an excellent grip. It is made in anodised aluminium with silver, gold or bronze finish with anodising coat of approx. 15/20 micron.

# PROEND GRIP

SILVER, GOLD and BRONZE ANOD. ALUMINIUM  
+ NON-SLIP INSERT  
ADHESIVE AND PUNCHED



**SILVER, GOLD and BRONZE ANODISED ALU. with adhesive thermo packed**

bar length 3,4 LM - pack. 20 Pcs - 68 LM

Article	H x L mm		
PEGR... 5230A	52 x 30		

**SILVER, GOLD and BRONZE ANODISED ALU. with adhesive thermo packed**

bar length 1,66 LM - pack. 20 Pcs

Article	H x L mm		
PEGR... 523016AS	52 x 30		



**SILVER, GOLD and BRONZE ANODISED ALUMINIUM punched thermo packed**

bar length 3,4 LM - pack. 20 Pcs - 68 LM

Article	H x L mm		
PEGR... 5230F	52 x 30		

**SILVER, GOLD and BRONZE ANOD. ALU. punched with screws and screw anchors thermo packed**

bar length 1,66 LM - pack. 20 Pcs

Article	H x L mm		
PEGR... 523016FS	52 x 30		



Available in the finish: AA - AO - AB. The code of the selected colour must be added to the article code. E.g.: PEGR... 523016AS (chosen finish Anod. silver) PEGRAA 523016AS.

The strip of adhesive carborundum (PROGRIP) is not applied. The roll of PGR 20 must be ordered separately (see below).

## COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)



**PROGRIP** is a self-adhesive product in carborundum consisting of a plastic film plus abrasive granules with high resistance to wear. It is normally used to guarantee safety on steps in public and private environments, as required by accident-prevention laws. Available in various colours and widths to meet all technical and aesthetic requirements. It is advisable to apply 2 strips on each step, rounding off the ends.




## ADHESIVE CARBORUNDUM NON-SLIP STRIP FOR STEPS

rolls length 18,2 LM

Article	Width mm		
PGRN 20 (black colour)	20		
PGRB 20 (white colour)	20		
PGR T 20 (transparent)	20		
PGRG 20 (grey colour)	20		
PGRY 20 (yellow colour)	20		
PGRM 20 (brown colour)	20		
PGRN 25 (black colour)	25		
PGRB 25 (white colour)	25		
PGR T 25 (transparent)	25		
PGRG 25 (grey colour)	25		
PGRY 25 (yellow colour)	25		
PGRM 25 (brown colour)	25		
PGRN 50 (black colour)	50		
PGRB 50 (white colour)	50		
PGR T 50 (transparent)	50		
PGRG 50 (grey colour)	50		
PGRY 50 (yellow colour)	50		
PGRM 50 (brown colour)	50		

## COLOURS




(for a precise assessment of colours and finishes, see the relative enclosed sheet)


## LAYING INSTRUCTIONS

1. Thoroughly clean and degrease the surface of application. 2. Round the ends of the strips. 3. Remove the protective paper from the adhesive and lay the PROGRIP using a roller. 4. Do not apply the strips at temperatures below 15°, otherwise heat the strips and the step. 5. When necessary clean away impurities with a brush and preserve the PROGRIP. 6. When laying on tiles, cut and round the corners of the strips on the inner part of the tile. 7. Carefully seal the outer edges of the strips to prevent water infiltration.

PEGR... 5230A/F



## EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the suitable profile for covering the edge of the step.
2. Clean the surface on which the profile is to be laid, ensuring that it is grease-free and dry. Do not apply the strips at temperatures below 15°.
3. Remove the protective paper from the adhesive and lay correctly by applying pressure evenly over the whole profile without using a hammer.

If the punched PROEND GRIP has been chosen, screw the profile to the step and apply the adhesive carborundum to hide the screws.

# PROGRIP

ADHESIVE CARBORUNDUM - 6 COLOURS



## EXAMPLES OF LAYING

