


POWER RAIZOR - MULTI-ANGLE CUTTING UNIT

MADE IN ITALY



433PWROH
Angle grinder not included



179CCT125



179FLEX45SERF



179FLEX45SE



179FLEX006SE

179FLEX010SE

179FLEX012SE

PACKAGE



- Multi-angle cutting unit to be used in combination to the RAIZOR cutting guide.
- It performs cuts with the following angles: 45° ("jolly", miter cut), 90° (standard/vertical cut), 180° (lateral incision - kerf/ slots along the side of the tile/slab, and/or side shaping - 1/2 bullnose).
- In addition to those positions, it also cuts at the following intermediate angles: 30°/47°/70°.
- Tilting movement (plunge cut) to adjust the depth of cut, to perform square and rectangular holes and to make cuts in multiple passes.
- Angle grinder not included.
- Suitable with the most popular brands and models of angle grinders.
- Available in 2 different versions to suit the following angle grinder arbor sizes: M14 (metric) or 5/8"-11 (imperial).

- Dry use (standard version) or wet use (to perform wet cut in combination with Kit for wet cut and dust suppression - Art. 433PWW A, Power Raazor must be equipped with cordless/battery operated angle grinder or corded model having rating IP54* or any higher).
- Includes connecting port for connection either to dust extractor or to Kit for wet cut and dust suppression (Art.433PWW A).
- Cutting depth (thickness): 20 mm (0.78") at 90°, 16 mm (0.63") at 45° and 180°.
- It comes supplied with Ø 125 mm (5") turbo blade, use and maintenance manual.


*Safety Regulations may vary from Country to Country. Therefore, it is strongly recommended to refer & comply to the legislation in force on the Country where the products is being used.

ACHIEVABLE CUTTING LENGTHS ACCORDING TO THE VARIOUS POSSIBLE COMBINATIONS OF POWER-RAIZOR AND RAIZOR + ITS EXTENSION


▼ 437 cm (14.34 ft.) | ■ 429 cm (14.07 ft.)




▼ 322 cm (10.56 ft.) | ■ 314 cm (10.3 ft.)



▼ 265 cm (8.69 ft.) | ■ 257 cm (8.43 ft.)



▼ 150 cm (4.92 ft.) | ■ 142 cm (4.66 ft.)



▼ 93 cm (3.05 ft.) | ■ 85 cm (2.79 ft.)



▼ plunge cut
■ no plunge cut

SPECIFICATIONS AND VERSIONS

Part No.	Box	Barcode	Description	Arbor	Disc	Angle	Extension 1	Extension 2	Extension 3	Weight	Dimensions	Weight
433PWROHEUD	1	8050532012233	POWER RAIZOR without angle grinder	M14	•	-	20 mm 0.79"	16 mm 0.63"	16 mm 0.63"	4,1 Kg 9 lbs	39x39x h14 cm 15 3/8"x15 3/8"x h 5 1/2"	4,7 Kg 10.3 lbs
433PWROHUSD	1	8050532012240	POWER RAIZOR without angle grinder	5/8"-11	•	-	20 mm 0.79"	16 mm 0.63"	16 mm 0.63"	4,1 Kg 9 lbs	39x39x h14 cm 15 3/8"x15 3/8"x h 5 1/2"	4,7 Kg 10.3 lbs

DIAMOND BLADES AND WHEELS

Part No.	Box	Barcode	Description	Profile	Ø	Arbor	Thickness	Use	Wet Cut	Dry Cut
179CCT125	1	8024648075703	Turbo diamond disc Ø 125 mm - 5" (f 22,2 mm) - included	-	125 mm	5"	-	-	•	•
179FLEX006SE	1	8024648094834	Shaping wheel for 1/2 bullnose	[Profile]	120 mm	4 3/4"	6 mm	1/4"	•	•
179FLEX010SE	1	8024648087171	Shaping wheel for 1/2 bullnose		120 mm	4 3/4"	10 mm	3/8"	•	•
179FLEX012SE	1	8050532010970	Shaping wheel for 1/2 bullnose	[Profile]	120 mm	4 3/4"	12 mm	1/2"	•	•
179FLEX45SE	1	8050532010987	Shaping wheel for 45° profile (jolly)		120 mm	4 3/4"	-	-	•	•
179FLEX45SERF	1	8050532011267	Finishing wheel for 45° profile (jolly)	[Profile]	120 mm	4 3/4"	-	-	•	•



TOOLS FOR LARGE FORMAT TILES



KIT FOR WET CUT AND DUST SUPPRESSION

- Wet cooling device to be used in combination with POWER RAIZOR and BC45.
- Blade cooling with water grants:
 - 1) Complete suppression of dust.
 - 2) Better cut finishing.
 - 3) Quicker cut.
- Both adjustments onto top and onto spraying nozzle allow a perfect cooling with a minimal amount of water.

- To be used only in combination with cordless (battery operated) angle grinders and/or corded models having rating IP 54* or any higher.
- It can be used with any cutting position/angle (45°/90°/180°).
- Carrytank capacity of 8 litres (1,75 gal) with relief valve.

*Safety Regulations may vary from Country to Country. Therefore, it is strongly recommended to refer & comply to the legislation in force on the Country where the products is being used.

SPECIFICATIONS AND VERSIONS

Part No.			Description	POWER RAIZOR	BC45	USE					
433PWZP A	1	8050532004573	Kit for wet cut and dust suppression	•	•	e/o	8 lt	1,75 gal	2,4 Kg	5.3 lbs	58x30x h25 cm 23"x12"x h 10"

DUST CONTAINMENT DEVICE

- Dust containment device to be used in combination with POWER RAIZOR cutting unit.
- Used in combination with a proper aspirator, it allows to radically reduce the amount of dust on the environment while dry cut is performed.
- The device can be used onto POWER RAIZOR equipped with any kind of angle grinder.

- Adjustable according with slab thickness.
- Can be used for 45° miter cut and 90° straight cut.

SPECIFICATIONS AND VERSIONS

Part No.			Description	POWER RAIZOR	BC45	USE				
433PWZP A	1	8050532004412	Dust containment device	•	—	All angle grinders	0,5 Kg	1.1 lbs	27x15x h10 cm	10 5/8"x6"x h 4"

